

## **4 CHANNEL IP CCTV KIT**

## **KIT INCLUDES:**

- 4pcs Dome/Bullet, 1080P IP Camera
- 1pcs 4ch 1080P POE NVR
- 4 X 20m Cables
- 15V 5A Power Supply
- English User Manual
- Mouse





Out-of-the-box four channel IP 1080p CCTV system including everything you need mini-network recorder, four 2.0 megapixel dome/bullet cameras, power supply, and cabling.

	NVR
OPERATING SYSTEM	EMBEDDED LINUX
SYSTEM RESOURCES	RECORDING, PLAYBACK, BACKUP, REMOTE VIEW, MOBILE VIEW
RECORDING	4CH*/1080P, 1920X1080 RESOLUTION
LOCAL PLAYBACK	4CH*720P/960P, 1CH*1080P PLAYBACK, 1280X960/1920X1080
	RESOLUTION
VIDEO IN	4CH BUILT-IN POE SWITCH FOR IP CAMERAS
VIDEO OUTPUT	1VGA, 1HDMI OUTPUT
RECORDING MODE	AUTO RECORDING, MOTION DETECTION RECORDING,
	MANUAL RECORDING
FREE DDNS	WWW.E-SEENET.COM
P2P/ESEE CLOUD	SUPPORT
LOCAL LOGIN	USER & PASSWORD
SUPPORT SYSTEM	IPHONE IOS, MOBILE, MICROSOFT WINDOWS XP, MICROSOFT
	WINDOWS 2000, ANDROID, WINDOWS7, WINDOWS 8
LANGUAGE	ENGLISH
DIGITAL ZOOM	SUPPORT
NETWORK	SUPPORT 3G, 5*RJ45 10M/100M ETHERNET
MOUSE CONTROL	SUPPORT
VIDEO SAVING	INTERNET, HARD DISK
BACKUP	USB DISK, HARD DRIVE, MOBILE, INTERNET.
USB2.0 INTERFACE	2
POWER SUPPLY	15V 5A POWER SUPPLY
POWER CONSUMPTION (W)	≤20W( NOT INCLUDING HDD )
OPERATE TEMPERATURE (°C)	-10°C~55°C
HUMIDITY (%) RH	>90%



BULLET CAMERAS & 8CH NVR'S ALSO AVAILABLE

## **KEY FEATURES**

- Full HD Video: 4\*1080P
- A-POE feature: Built-in switch, Power and Video via One Cable
- Plug and play
- Eseenet P2P Remote Viewing
- No need for port forwarding or DDNS setting
- Mobile viewing iPhone & Android app
- Free DDNS www.e-seenet.com

	CAMERA
SENSOR	CMOS
MEGA PIXEL	2.0 MEGA
DUAL-STREAM	MAIN STREAM:1080P 25FPS, SUB STREAM: 640*480
IMAGE RESOLUTION	1920X1080
VIDEO COMPRESSION	H.264
LENS	3.6MM
IR	24 X Φ5MM LEDS
DAY/NIGHT	25-30 METERS IR NIGHTVISION
FREE DDNS	WWW.E-SEENET.COM
WATERPROOF	IP66
VIDEO BIT RATE	64KBPS-4096KBPS CONTINUOUSLY-ADJUSTABLE
PRTCOL/NETWORK FUNCTION	RTSP, UPNP, PPPOE, DDNS
WEB BROWSER	CHROME, SAFARI, FIREFOX
MOBILE SURVEILLANCE	SUPPORT IPHONE, ANDROID
NETWORK	RJ45 10M/100M ADAPTIVE ETHERNET INTERFACE
OPERATING ENVIRONMENT	-10°C- +55°C/10%-90%
POWER SUPPLY	DC12V,1A (OPTIONAL)/POE POWER
POWER CONSUMPTION	6W

## JUST PLUG & CONNECT

The connector system makes it easy for installers to set up the cameras on the system. Just connect the camera cable to the 20m cable run, twist and lock the cover together and you have a weatherproof connection between the camera and recorder.

PLACE AN ORDER WITH OUR SALES TEAM - sales@eufireandsecurity.com

**EU Fire & Security Ltd** - **N** 01706 658880

01706 658918

www.eufireandsecurity.com