

CAP320, CAPT340, CAH330

Intelligent addressable sensors



Our addressable range has multiple options for intelligent addressable sensors. All sensors are designed for optimum functionality in mid-large sized builds. They are all soft addressed and have integral short circuit isolators.

This range of intelligent addressable sensors have been specifically designed to operate with Eaton intelligent addressable fire systems. All sensors are third party approved to the relevant section of EN54 (part 7 for smoke detectors & part 5 for heat detectors).

Features and benefits

- Soft addressed
- Integral short circuit isolator
- Single address
- Wide range of sensor types
- 360° visibility LED using lightpipe technology
- Drift compensation
- Aesthetically pleasing
- Quick and simple to install
- Single "multi-mode" heat sensor
- Wide viewing angle for increased LED visibility
- Common mounting base
- Positive "lock" indication
- Discreet design for incorporation into any decor
- Easy to maintain/service

Specifier's guide

2.4 Accessories

Optical smoke sensor (CAP320)

The optical sensor is suitable for most applications giving the fastest response to slow burning or smouldering fires which give rise to large visible smoke particles.

Heat sensor (CAH330)

The heat sensor can be set to one of 3 modes 77°C / 92°C and rate of rise. These sensors are designed to be used in environments where the ambient conditions might cause false alarms if smoke detection were to be used, for example where there is a high level of dust, fumes, steam or smoke under normal conditions.

Photo thermal sensor (CAPT340)

The photo-thermal sensor will respond quickly to fast clean burning fires yet maintain the advantage of optical sensors when detecting smouldering fires. The thermal enhancement of this sensor allows a higher alarm threshold which provides a greater rejection of false alarms. The sensor will also raise an alarm at temperatures exceeding 60°C.

The CAPT340 has day/night modes available, programmable from the site installer software. The day mode uses the heat aspect of the sensor for areas which may have smoky environments during, for example working hours. The night mode uses a combination of A2S and smoke detection. If not programmed, the sensor defaults to dual mode.

Technical specification

Code	CAP320	CAPT340	CAH330
Description	Optical smoke sensor	Photo-thermal sensor	Multi-mode heat sensor
Standards	EN54 Pt7 2000 + A1:2002, EN54 Pt17	EN54 Pt7 2000 + A1:2002, EN54 Pt17	EN54 Pt7 2000 + A1:2002, EN54 Pt17
Operating voltage	18V dc to 30V dc	18V dc to 30V dc	18V dc to 30V dc
Standby current	220µA (max)	220µA (max)	220µA (max)
Alarm current	5mA (max)	5mA (max)	5mA (max)
Addressing mode	Auto address	Auto address	Auto address
Specification			
Mounting position	Ceiling in open areas	Ceiling in open areas	Ceiling in open areas
Mounting options	Surface mount with CAB300 base	Surface mount with CAB300 base	Surface mount with CAB300 base
Area coverage	100m ² (subject to local standard)	100m ² (subject to local standard)	100m ² (subject to local standard)
System wiring	Min. 1.5mm, 2 core loop or spur	Min. 1.5mm, 2 core loop or spur	Min. 1.5mm, 2 core loop or spur
Heat class			
Rate of rise	N/A	A1S	A1R
Fixed heat 77°C	N/A	N/A	BS
Fixed heat 90°C	N/A	N/A	CS
Alarm temperature (static)			
AIR	N/A	60°C	60°C
BS	N/A	N/A	77°C
CS	N/A	N/A	90°C
Indication	360° visibility light pipe	360° visibility light pipe	360° visibility light pipe
Environmental			
Operating temperature	-10°C to +60°C	-10°C to +50°C	-10°C to +60°C
Humidity (non condensing)	0 to 95% RH	0 to 95% RH	0 to 95% RH
Physical			
Construction	PC/ABS	PC/ABS	PC/ABS
Colour - RAL no.	White - 9003	White - 9003	White - 9003
Dimensions excel base (Dia x D)	101mm x 33mm	101mm x 43mm	101mm x 43mm
Dimensions incl base (Dia x D)	104mm x 45mm	104mm x 55mm	104mm x 55mm
Weight (without base)	76g	76g	76g
IP rating	IP30	IP30	IP30
Compatibility			
Suitable for use with	Eaton intelligent addressable fire systems	Eaton intelligent addressable fire systems	Eaton intelligent addressable fire systems

Dimensions

Description	Dia (mm)	D (mm) (excl base)	D1 (mm) (incl base)
Optical	101	33	45
Photo-thermal	101	43	55
Multi-mode heat	101	43	55

Catalogue numbers

Description	Code
Optical smoke sensor	CAP320
Photo/thermal sensor	CAPT340
Multi-mode heat sensor	CAH330
Standard base	CAB300
Conventional remote indicator	CIR301
Duct probe (requires detector & base)	MDP201
Loop connected remote indicator	MRIAD