## **Low Profile Single-sided LED Exit Box**



**LEGENDS (SOLD SEPARATELY)** 

EL-1012 EL-1013

EL-1014

EL-1015

## **FEATURES**

- Zintec plated sheet steel construction in white epoxy finish
- Rear centre besa entry and keyhole slots for ease of installation
- Single Polycarbonate Legends available (sold separately)
- Opal polycarbonate panel illuminates directly below the sign to the escape route and door threshold
- Legend panel can be removed from either end via removable end-caps
- TM-21 L70 greater than 36,000 hours using 0.5W 150 lumen/Watt LEDs
- CRI 80 (minimum) and 3 step MacAdam rated
- 6500K colour temperature as standard

GENERAL	Country Of Origin: CE Mark Compliance: Manufactured to Standards: Manufacturing Quality Approval:	United Kingdom CE marked REACH and RoHS compliant EN60598-2-22: 1999 ISO9001:2008
SPECIFICATION	Light Source & Mode: Emergency Lumens: Colour Temperature: Weight:	5 x 0.5W LED M3 90 6500K 2.5Kg
CONSTRUCTION	Housing Construction: Diffuser Material: Body Finish: Protection Degree: Insulation Class & Supply Voltage: Internal Cabling:	Mild steel Self-extinguishing polycarbonate White powder coated IP20 Class 1 230/240V AC 50/60Hz 105°C single core 0.8mm to BS6500 Grade 5
DIMENSIONS (mm)	200mm  Viewing Distance: 36 Metres	



Tel: 01706 658 880 Email: sales@eufireandsecurity.com