## Non-Maintained 3hr 2 x 7W LED Twin-Spot



## **FEATURES**

- IP65 Rated enclosure
- High quality Nickel Cadmium battery cells
- 3 hours non-maintained emergency duration
- Swivel/tilt heads enable the client to tailor light distribution to highlight specific areas
- Low Voltage disconnect circuit prevents batteries entering deep discharge state in the event of prolonged power failure
- Constant current with green LED to indicate mains is healthy and battery is connected
- High quality polycarbonate lenses

| GENERAL         | Country Of Origin:<br>CE Mark Compliance:<br>Manufactured to Standards:<br>Manufacturing Quality Approval: | United Kingdom<br>CE marked REACH and RoHS compliant<br>EN60598-2-22: 1999<br>ISO9001:2008                  |
|-----------------|--|---|
| SPECIFICATION   | Light Source & Mode:<br>Emergency Lumens:<br>Colour Temperature:<br>Weight:                                | LED NM3<br>2 x 626<br>7000K<br>3.80Kg   |
| CONSTRUCTION    | Housing Construction: Body Finish: Protection Degree: Insulation Class & Supply Voltage: Internal Cabling: | Polycarbonate<br>White<br>IP65<br>Class 1 230V/240V AC 50/60Hz<br>105°C single core 0.8mm to BS6500 Grade 5 |
| DIMENSIONS (mm) | 294mm  |   |
|                 | 300mm  | 69mm  |

| EL-1003 | Mounting Height (m) | Trans to wall | Trans to trans |              |
|---------|---------------------|---------------|----------------|--------------|
|         | 4                   | 5             | 15             | 1 lux min.   |
|         | 6                   | 4             | 16             |              |
|         | 4                   | 7             | 14             | 0.5 lux min. |
|         | 6                   | 8             | 16             |              |



For further information and sales, please contact us:

Tel: 01706 658 880 Email: sales@eufireandsecurity.com