

PRODUCT CODE
EL-1004

Non-Maintained 3hr LED Open Area 3W Downlight



FEATURES

- Luminaire diameter of just 50mm and emergency packs can easily pass through a ceiling cut-out of 40mm
- Superbly designed lens ensures less luminaires are required per installation
- Unique optical design to optimise the light distribution for emergency lighting applications
- Specially developed LED driver and advanced thermal engineering techniques reduce LED operating temperatures
- Supplied as an open area version as standard with corridor versions to illuminate centre lines of escapes routes available as an option
- Polycarbonate body and diffuser are 850°C hot-wire compliant
- High performance LEDs exceed 36,000 hours in accordance with TM-21
- Boasts mounting heights in excess of 5 metres to achieve 0.5 lux
- Emergency versions utilise Nickel Cadmium battery packs

APPLICATIONS

Corridors
Offices
Retail

SPECIFICATION

3W Circuit Power (85 lumens)
Colour Temperature: 6500k
Weight: 1.10kg


CONSTRUCTION

850°C polycarbonate body and diffuser
White body
IP20 Rated
Class 1 230/240V 50/60Hz

CERTIFICATION

Compliant with EN60598.2.22: 2008. CE marked REACH and RoHS compliant

DIMENSIONS (mm)



Luminaire

A: Ø 50mm x B: Depth 32mm (10mm below ceiling)

Emergency Pack

Ø 38mm x Length 600mm

Cut-Out

Ø 40mm