FB Bell - Electronic Solenoid


A unique, patented alarm bell designed for use in fire, security and other signalling systems. The combination of a miniature solenoid with an integrated control circuit allows excellent sound coverage, minimum current consumption and increased reliability. The improved aesthetics make the bell suitable for all applications including the most prestigious locations.




Technical Specification

Voltage	12Vdc 24Vdc 230Vac	
Current	12 Vdc 55 - 65mA 24 Vdc 25 - 35mA 230 Vac 20 - 30mA	
Sound Output	93 - 95dB(A)	
Monitoring	Reverse polarity (dc only)	
Temperature	- 25°C to + 70°C	
Protection	IP21C / IP33C (WP)	
Construction	Gong -steel, base - polycarbonate	
Weight	12 Volt 1.1Kg 24 Volt 1.1Kg 230 Volt 1.2Kg	
Colours	Gong - red Base - black	







Features

- Modern design
- Clip together assembly
- Weatherproof kit option
- High "ring" output

Benefits

- Suitable for all locations
- Easy to fit
- Provides protection up to IP33C for external use
- Easily identified signal

Reference	Catalogue No.	Description
FB/12 RED	500001FULL-0001	Electronic Solenoid Bell, 12Vdc, Red
FB/230/RED	504001FULL-4001	Electronic Solenoid Bell, 230Vac, Red
FB/12/RED/WP	500003FULL-0003	Weatherproof Electronic Solenoid Bell, 12Vdc, Red
FB/24/RED/WP (CPD Certified)	506001FULL-6001	Weatherproof Electronic Solenoid Bell, 24Vdc, Red
FB/230/RED/WP	508001FULL-8001	Weatherproof Electronic Solenoid Bell, 230Vac, Red

