

Summit

Smoke detection for the deaf.

The Mains Smokie Domestic System.(SM011-B)

The Mains Smokie is supplied complete with a compact wall or table mounted control unit with an integral powered flashing beacon, a pillow-vibrating pad and a ceiling mounted smoke detector.

The unit is complete and ready to install.

The small mains powered control unit has a sealed rechargeable battery back up, automatically kept in fully charged condition in case of mains power failure.

The smoke detector is powered from the central control unit the system is completely independent of replacement batteries.

All connections are permanently monitored to ensure that the system is operating correctly.

The smoke detector is powered from the central control unit the system is completely independent of replacement batteries. All connections are permanently monitored to ensure that the system is operating correctly.



Variations of the Smokie SMO11-B:

SM011-B: (as above) Mains powered with a sealed battery backup, to protect against mains failure. The smoke detector is powered from the control unit and does not require batteries. This unit is ideal where maintenance free operation is required.

SM011-M: (as above), to interface with an independent mains powered smoke detector head.

SM011-24: (as above) designed for 24volt central fire alarm systems, linking directly to the existing fire bell alarm circuit.

Product	Order Code
Mains Smokie	SM011-B
SM011-M	SM011-M
SM011-24	SM011-24

All versions of the SM011 can be fitted with carbon monoxide detectors and heat sensors

Pad & Plate: Commercial Use.

Single Gang Plate: The plate is designed for connection across the bell circuit of commercial fire alarm systems. The plate is a standard single gang design. The plate and its vibrating pad operate at 24 volts DC and consume 120mA when operating.



The Vibrating Pad:

The positioning and securing of the pad is very important, it is the main means by which the user is woken in the event of a fire.

Commercial Use: Hotels, Halls of Residence, Care Homes, Sheltered Accommodation etc.

Variations the Vibrating Pad

Product	Order Code
6v Vibrating Pad 3.5mm Jack	V/B - 6v - LJP
12v vibrating Pad 2 pin JST	V/B - 12 - JST
24v Vibrating Pad 3 pin mini XLR	V/B - 24 - XLR
Single Gang Plate Mini XLR	V/B - SGP - XLR

Quantity prices available on application



Specials:

Plates can be made to suit individual requirements.
The plate shown is Lacquered brushed stainless steel.

Please contact us to discuss your requirements.

Summit Deaf Aids

Waterfront Studios, 54C Dock Road, London. E16 2AA

Tel. 0207 474 5552. Fax 0207 474 2666. email sales@summitdeaf aids.co.uk

We are: ISO 9001-2008 accredited Wee Registered: WEE/UP3838PL/SCH