

CAST Zone Monitor Module

Part No. **CA732**



Overview

- LPCB certified to EN54-17 & 18 and Kiwa Telefication & DBI certified to EN54-13.
- Also certified to the relevant parts of EN54 with Swedish certification body SBSC.
- A single-zone addressable Zone Monitor capable of supporting up to 20 conventional fire detectors and 10 MCPs
- Mountable on a standard UK 25mm double gang back box.
- Onboard short-circuit loop isolator.
- 4mA typical alarm current (1.1mA typical quiescent current) @ 22-40V DC.
- Indicators for Loop polling, input faults and relay status.
- Alternatively, can be used as general purpose input monitor.
- Mountable on a C-TEC NCP-26 surface box or a standard UK 25mm double gang back box (not supplied).



More Information

'CAST' is the world's most-advanced 'distributed intelligence' fire alarm system protocol. Conceived, designed and realised by C-TEC, it involved the creation of a powerful proprietary communication protocol (C-TEC Addressable System Technology, CAST) and multiple control panels & field devices. Its key features include:-

- 255 devices per loop.
- Autonomous decision-making for faster response times.
- Multiple type codes.
- 40V loop drive voltage.
- Two 'soft' addressing options - automatic via the panel or manual via a powerful handheld programmer.
- Powerful multi-level addressing facilitates easy device addition and swapped device identification.
- Multiple functionality at a single address (integrated devices) via our CAST-PRO devices.
- Volumes, tones & detector modes can be changed at compatible panels.
- High-speed data transmission and robust data transfer.
- Intrinsically EN54-13 compliant.
- Geographical location of short and open circuit faults (a short circuit isolator is included as standard in every CAST field device).



Replace device function. • Future seamless integration with other CAST life safety systems reducing energy, servicing, installation and repair costs. • Designed and manufactured in the UK.

Technical Specifications

Approvals/certifications	Certified by SBSC to the relevant parts of EN54, DBI certified to EN54-13, LPCB certified to EN54-17 & 18 and Kiwa Telefication certified to EN54-13
Compatibility	Compatible with C-TEC's XFP/ZFP CAST Addressable Fire Panels.
Application/operation	A single-zone addressable Zone Monitor capable of supporting up to 20 conventional detectors and 10 manual call points.
Supply/operating voltage	22 to 40V DC.
Quiescent current	1.1mA typical.
Activation current	4mA @ 22-40V DC.
Auxiliary relays	None.
Auxiliary inputs	One monitored input that can be set to operate as a single zone monitor to support up to 20 ActiV detectors.
Indicators	Active (Lit Red): relay activated; monitored zone triggered or monitored switch closed; Polling (Flashing Red): communication check with the panel; Input Fault (Lit Yellow): fault detected
Connections	Six 45° screw-type connectors that can take 0.5-2.5mm ² cable: +Ve & -Ve Loop In; +Ve & -Ve Loop Out; Zone +Ve & -Ve.
Product dimensions (mm)	147 W x 87H x 22 D mm. Can be mounted on a standard 25mm UK flush or surface double gang back box.
Construction & finish	ABS Polycarbonate plate with a 200 micron two-tone grey velvet polyester label with red and white detailing.
IP Rating	IP40 when correctly installed.
Weight	122g.
Operating conditions/temperature	-10°C to +55°C.

