

Electro-Magnetic Locks

Code: AEM20002



EM | Slimline | Single | Monitored



Electro-Magnetics Locks are electrified locking devices which consist of an electro-magnet and an armature plate to lock a door when powered up, then released by a device such as a push to exit button or keypad.

Features & Benefits

- CQR Slimline Electro-Magnetic Locks
- Available in monitored & un-monitored versions
- Suitable for medium use traffic applications
- 12/24V DC Self-Regulating
- 5 year warranty
- Optional brackets & accessories available



Product Information

Warranty	5 Years
Range	Slimline
Door Supported	Single
Status	Monitored
Type Of Magnet	Face Fixed EM Lock
Finish	Satin Anodised Aluminium

Technical Data

Magnet Size (L x W x D)	L250 x H50 x D27
Length (mm)	250
Width (mm)	50
Depth (mm)	27
Nom Holding Force (Per Door)	285kgf/628lbf
Input Voltage	12/24V DC
Input Current	12V = 500mA (+/-10%) 24V = 250mA (+/-10%)

Suitable Brackets

L Bracket	SLM/L
Z & L Bracket	SLM/ZL
Architectural L Bracket	SLM/L/ARC
Architectural Z & L Bracket	SLM/ZL/ARC
Surface Armature Plate	SLM/AH

Certifications

CE Marked	Yes
UKCA Marked	Yes
Fire Test	EN1634-1
Fire Rating	E30 & E60
RoHS Compliant	Yes
EMC	EMC

