



## Downlight Spot: Recessed

*Code: SP/1/NM/WH/865*

WHITE - Spot LED Emergency Downlight, c/w open area & corridor lens

CQR Emergency Downlights are available as discreet non-maintained spot lights and our range of Escape surface mount downlights allows for mounting on cable trays / baskets in open ceilings with much higher lumen outputs. The Escape and Spots fittings are both available in black and white and come with both corridor and open area interchangeable lens as standard to maximise optionality and ease for our installers.

### Features & Benefits

- Emergency Downlight Spot: Recessed
- Supplied with Open Area Lens (120lm) and Corridor Lens (130lm) as standard
- Foldable converter: easy to install
- Non-maintained fitting
- 5 years warranty: full fitting and battery
- Available in black and white
- Self-test functions available



## Technical Data

|           |    |
|-----------|----|
| IP Rating | 20 |
|-----------|----|

## Electrical

|                         |                      |
|-------------------------|----------------------|
| Battery                 | LiFePO4 3.2V 1500mAh |
| Voltage / Frequency     | AC 220-240V 50/60Hz  |
| Running Current (A)     | 0.01                 |
| Charging Power (W)      | 1.2                  |
| Emergency Power (W)     | 1                    |
| Standby Power (W)       | 0.4                  |
| Power Factor            | 0.34                 |
| Inrush Current (A / us) | 3                    |
| Electrical Class        | 2                    |

## Features

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

## Photometric Data

|                             |                                    |
|-----------------------------|------------------------------------|
| Emergency Mode Lumens       | Open – 120 / Corridor - 130        |
| CCT (K)                     | 6500                               |
| Beam Angle                  | Open – 165° / Corridor – 160 x 50° |
| Lumen Maintenance L80 (Hrs) | 50000                              |
| CRI                         | 80                                 |

## Emergency

|                             |                |
|-----------------------------|----------------|
| Emergency Duration (Hrs)    | 3              |
| Maintained / Non-Maintained | Non-Maintained |
| Test Button                 | No             |
| Self-Test                   | No             |

## Mechanical

|                       |               |
|-----------------------|---------------|
| Mounting Method       | Recessed      |
| Housing Material      | Polycarbonate |
| Dimensions (LxWxH mm) | 250x36x27     |
| Dimensions (DxH mm)   | 50x21         |
| Cutout Size (DxH)     | 40x30         |



## Warranty

### Product Warranty

5

