

Evacuation Alert System Mains Isolator Keyswitch

Part No. **EAP326/WS**



Overview

- Allows the mains to an Evacuation Alert panel to be switched on or off.
- Supplied with a surface mounting back box.
- Third-party tested to the relevant insulation and isolation requirements of IEC/EN 60669.
- Double pole.
- Fitted with a 5A Fuse.
- Supplied with a special key that is only available to the responsible person.
- Able to be wired with 1 x 2.5mm² cable or 2 x 1.5mm² cable to ensure only independent sole main supplies are used to the Evacuation Alert panel.



Technical Specifications

Approvals/certifications	Third-party tested to the relevant insulation and isolation requirements of IEC/EN 60669
Type	Double pole, lockable, 230V
Mains rated current	5A.
Supply/operating voltage	230 VDC.
Quiescent current	2mA if LED, 0mA if no LED,
IP Rating	IP30.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Construction & finish	White PVC.
Product dimensions (mm)	Switch Plate 86 x 86 mm x 25 or (25.7mm deep with LED), with supplied back box fitted 54mm deep.
Weight	TBC.



Notes

Key type: Red C-TEC S-Key.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: sales@c-tec.co.uk
c-tec.com

You're Safe with C-TEC

